

MS9540 Voyager CG

Single-Line Laser Scanner

Honeywell's MS9540 VoyagerCG® hand-held, single-line laser scanner offers aggressive scanning of all standard 1D bar codes.

The Voyager series of hand-held, single-line scanners have united form with function in becoming the industry benchmark for value and performance.

This sleek scanner features patented automatic infrared activation and decodes all standard 1D bar codes, including GS1 DataBar[™] (formerly known as RSS codes).

VoyagerCG also includes patented CodeGate® technology which allows the user to easily target the desired bar code and complete data transmission with the press of a single button.

For presentation scanning, Honeywell offers a stand with automatic in-stand detection technology

The MS9541 VoyagerHD™ is ideal for applications that require high-density scanning, delivering quick and accurate scanning of 1D bar codes as small as 3 mil.

Expand scanner functionality by purchasing the MS9544 VoyagerPDF™, which delivers aggressive scanning of all standard 1D bar codes including PDF.

For more information on the MS9540 VoyagerCG single-line laser scanner, please visit www.honeywell.com/aidc



Features

- Automatic Trigger: Use scanner as either a hand-held device or a fixed presentation scanner when mounted in the stand
- 650-nanometer laser: High-visibility laser allows user to place laser line on selected bar code
- CodeGate: Zero in on desired code and complete data transmission with the push of a single button—ideal for menu scanning applications
- Flash ROM: Future proof POS system with free firmware updates via MetroSet®2 software and standard PC
- Parsing (Data Editing): Format bar code data to meet host system's specific requirements

MS9540 VoyagerCG Technical Specifications

| Operational | | |
|---------------------------|---|--|
| Light Source | Visible Laser Diode 650 nm ± 10 nm | |
| Visual Indicators | Green = ready to scan; Red = good read; Yellow = automatic scanning | |
| Host System Interfaces | USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA, Laser Emulation, Light Pen Wand Emulation | |
| Mechanical | | |
| Dimensions (LxWxH) | 198 mm x 78 mm x 56 mm (7.8" x 3.1" x 2.2") | |
| Weight | 149 g (5.3 oz) | |
| Electrical | | |
| Input Voltage | 5 VDC ± 0.25 V | |
| Operating Power (typical) | 825 mW (165 mA @ 5 V) | |
| Standby Power (typical) | 600 mW (120 mA @ 5 V) | |
| DC Transformers | Class 2: 5.2 VDC @ 1 A | |
| Laser Class | Class 1: IEC60825-1, EN60825-1 | |
| EMC | FCC Part 15, ICES-003, EN55022 Class B | |
| Environmental | | |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) | |
| Storage Temperature | -40°C to 60°C (-40°F to 140°F) | |
| Humidity | 5% to 95% relative humidity, non-condensing | |
| Drop | Designed to withstand 1.5 m (5') drops | |
| Environmental Sealing | Sealed to resist airborne particulate contaminants | |
| Light Levels | 4842 Lux (450 foot-candles) | |
| Scan Performance | | |
| Scan Pattern | Single scan line | |
| Scan Speed | 72 scan lines per second | |
| Scan Angle | Horizontal: 50° | |
| Print Contrast | 35% minimum reflectance difference | |
| Pitch, Skew | 68°, 52° | |
| Decode Capabilities | Reads standard 1D and GS1 DataBar symbologies. PDF417 reading available in MS9544 only. Visit www.honeywell.com/aidc/symbologies for details. | |
| Warranty | 5 year factory warranty | |



For more information:

www.honeywell.com/aidc

| MS9540 / MS9544 Typical Performance* | | |
|---|-------------------------------|--|
| Narrow Width | Depth of Field | |
| 5.2 mil | 13 mm - 51 mm (0.5" - 2.0") | |
| 7.5 mil | 0 mm - 127 mm (0" - 5.0") | |
| 10.4 mil | 0 mm - 165 mm (0" - 6.5") | |
| 13 mil | 0 mm - 203 mm (0" - 8.0") | |
| 21 mil | 25 mm - 254 mm (1.0" - 10.0") | |
| *Resolution: 5 mil (0.127 mm) *Performance may be impacted by bar code | | |

| MS9541 Typical Performance* | | |
|---|----------------------------|--|
| Narrow Width | Depth of Field | |
| 4.0 mil | 6 mm - 38 mm (0.3" - 1.5") | |
| 6.8 mil | 0 mm - 76 mm (0" - 3.0") | |
| 10.4 mil | 0 mm - 108 mm (0" - 4.3") | |
| 13 mil | 0 mm - 140 mm (0" - 5.5") | |
| | | |
| *Resolution: 3 mil (0.076 mm) *Performance may be impacted by bar code quality and environmental conditions | | |

Honeywell Security & Data Collection

Honeywell Scanning & Mobility 90 Coles Road Blackwood, NJ 08012 856.228.8100 www.honeywell.com

