

***POSIFLEX***

A Robust, Economical Choice



## PS-3415/3415E

Best Value Fanless POS Terminal

The PS-3415 Series is a 15" fanless touch POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represents one of the best value choices in the entry-level POS Terminal segment.

# PS-3415/3415E

Specification		PS-3415	PS-3415E
Processor		Intel Bay Trail J1800 Dual Core CPU, up to 2.58 GHz, 1M Cache	Intel Bay Trail J1900 Quad Core CPU, up to 2.42 GHz, 2M Cache
System Memory		DDR3L SO-DIMM x 1, max. 4GB	DDR3L SO-DIMM x 1, max. 8GB
Storage Device		SATA x 1	SATA x 1, SATA SSD default
Power Supply		12V/40W	
OS Support		Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request	
Display & Touch			
LCD		15" TFT LCD	
Resolution		1024 x 768	
Touch		True-flat PCAP touch with multi-touch support (IP65 on front panel)	
I/O & Expansion			
Serial Port		4, DB9 x 3 + RJ50 x 1, 5V/12V support on all COM ports	
Parallel Port		1, via optional conversion cable through service window	
Standard USB Port		USB 2.0 x 5	
PoweredUSB Port		Optional 24V x 1 + 12V x 3 via GEN8 base	
OTG USB		N/A	
LAN Port		10/100/1000 Mb x 1	
Display Port		VGA x 1, 12V support for Posiflex monitors	
CR Port		1, control 2 CR via optional Y-cable	
PS/2 Port		1, via optional conversion cable through service window	
Audio		Buzzer only	
Expansion Slot		N/A	
Physical Dimension			
Dimension (W x D x H in mm)		372 x 320 x 252.7	
Weight (N. W. in kg)		5.86	
Environmental			
Operating Condition		0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition		-20°C - 70°C, 10%RH - 90%RH	
Built-in Options			
WiFi		USB WiFi dongle	
Attachment Options			
POS Monitor		Non-touch TFT USB LCD: 7"/9.7"	
Line Display		2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display	
Attachment		MSR; iButton; RFID; Fingerprint Sensor; Keypad	

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

\*The product information and specifications are subject to change without prior notice.

\*Please refer to the website for more attachment options.

Certifications	      	EN202101V1
----------------	--	------------

**POSIFLEX**

**POSIFLEX TECHNOLOGY, INC.**

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan  
 Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw  
 Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller